

RESIDENTIAL BATTERY
Alpha 16

Low Voltage

Alpha 16



Voln^ex
ENERGY STORAGE SYSTEM



Top-notch LFP Class A cell
/ Strict capacity grading



100% tested for safety,
readability and
capacity



Auto aerosol fire extinguishing
Ultimate security, strengthen
defense



Real-time data
monitoring and
firmware update



Full automatic
manufacturing
Products



Precise voltage/temperature
/SOC detection



One button start/stop and
parallel connection



Touch LCD display
shows data visually

DATASHEET

Model		Alpha 16
Performance		
Cell technology		LFP (LiFePO ₄)
Battery usable energy [1]		16076.8 Wh
Cell Capacity		314 Ah
Nominal voltage		51.2 Vdc
Operating voltage		44.8 ~ 56.16 V
Max. charge and discharge current [2]		200 A
Communication		
Display		SOC status indicator, LED indicator, LCD display
Communication		CAN / RS485 / RS232 / Wi-Fi
General Specification		
Dimension (W×D×H)	485×245×785 mm	
	19.1×9.6×30.91 inch	
Weight		122 kg (265.96 lbs)
Installation		Floor stand
Operating temperature [3]		Charge: 0 to 50°C (32 to 122°F) Discharge: -15 to 50°C (5 to 122°F)
Environmental humidity		≤ 95%RH (No condensation)
Ingress protection rating		IP20
Cycle Life		6000 Cycles @ 80%DOD / 25°C / 0.5C 60% EOL
Warranty Period [4]		10 years warranty (5 years product + 5 years service)
Scalability		Max. 15 batteries in parallel
Application		ON Grid / ON Grid + Backup / OFF grid
Compatible inverters		Refer to compatible inverter list (Compatible with major PCS brands)
Standard Compliance		
Compliance		UN38.3 / IEC62619 / IEC61000 (More available upon request)
Ordering and Delivery Parts		
Parts	Alpha 16 Battery	
	Alpha 16 Parallel cable	
	Alpha 16 to PCS cable	

[1] Test conditions: 100% depth of discharge (DOD), 0.2C rate charge & discharge at 25°C.

[2] There is 0.5C or 1C configurations optional in factory default.

[3] Charge/discharge derating occurs when the temperature is below 0°C or above 45°C.

[4] Please refer to the Warranty Letter for applicable conditions.

